



TR-004	
CPU	Micro processor with hardware RAID
Drive Bay	4 x 3.5-inch SATA 3Gb/s
Drive Compatibility	3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s solid state drives
Hot-swappable	Yes
USB 3.2 Gen 1 port	1 x Type-C USB 3.2 Gen 1 (USB 3.2 Gen 1)
Form Factor	Tower
Dimensions (HxWxD)	168.5 × 160.2 × 219 mm
Weight (Net)	1.85 kg
Max. number of HDDs/SSDs supported	4
Hard Drive Type	4 x 2.5-inch or 3.5-inch SATA 3Gb/s
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	65W adapter (12VDC), 100-240VAC
Power Consumption: HDD Sleep Mode	4.17 W
Power Consumption: Operating Mode, Typical	18.21 W
Fan	1 x 120mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.