# HP P24v G5 FHD Monitor



**Everyday Productivity** 

Expand your view and your productivity with this 23.8-inch diagonal, FHD monitor when you're working from home or at the office. This sleek monitor makes hybrid work easy and complete via a crisp, smooth screen and simple design, so you can do more everyday.



\*Product image may differ from actual product

# In Full View

• Enjoy a productive, hybrid work experience with excellent front-of-screen views. This monitor boasts FHD resolution and 75Hz refresh rate<sup>1</sup> for sharp images and fluid motion.

## Modern Design. Functional Fit.

• Clear your mind and your desk with a monitor designed to work in any space. Keep the focus on your screen through the sleek 3-sided micro-edge bezel, neat cable management, and slim stand with adjustable tilt for your perfect view.

# Easy Control. Easy Management.

Make your workspace as simple as possible, so you can concentrate on what you do best. Easily setup your monitor
by customizing your settings with the intuitive Joypad OSD button or manage settings and updates directly from
the screen with HP Display Center<sup>2</sup> and Display Manager<sup>3</sup>.

## Reduce. Repurpose. Recycle.

To do more for the planet, we are helping to close the loop by repurposing IT equipment in our newest EPEAT<sup>®</sup> registered<sup>4</sup> and ENERGY STAR<sup>®</sup> monitors. To go above and beyond, these monitors contain 85% recycled plastics solely from recycled ITE plastics<sup>5</sup>. Plus, this monitor ships in 100% recyclable packaging<sup>6</sup>.

# Featuring

#### 75 Hz Refresh Rate

Experience smooth, life-like video and clear detail with a 75 Hz refresh rate that provides fluid movement from frame to frame.<sup>1</sup>

#### 3-Sided Micro-Edge Bezel

See and do more on your screen with a 3-sided micro-edge bezel that maximizes your viewing area for a sleek design and seamless dual-monitor setups.

#### Easy Joypad OSD Button

It's never been easier to configure your display with the Joypad OSD button to adjust brightness, resolution, and volume.

#### Low Blue Light Mode

Keep your eyes comfortable with subtly warmer display colors onscreen.

#### With the Environment in Mind

Meeting the latest standards with EPEAT® registered, ENERGY STAR® and TCO certifications.<sup>4</sup>

#### Thoughtful Product Packaging

We use 100% recyclable packaging that meets recycling requirements, so it can stay out of the landfill.<sup>6,7</sup>

#### Neat Cable Management

Neat cable management solution for a cleaner workspace and more productivity.

#### HP Display Manager

Manage deployment, asset tracking and monitor settings remotely.<sup>8</sup>

#### **HP Display Center**

Customize your display with easy, intuitive HP Display Center software that lets you tailor your settings, partition screens, and even dim the screen.<sup>2</sup>

#### HP B200 PC Mounting Bracket

Save space by attaching the B200 bracket to the base of the monitor and your PC.<sup>9</sup>

# HP P24v G5 FHD Monitor Specifications Table



Displeytype         VA           Panel Active Area         52.55 v. 20.5 cm           Sprinters         25.0 mcl           Contrast nuit         3000.1 <sup>1</sup> Response Ratio         Sm Std G (with over/lwol) <sup>1</sup> Poduct colour         Black           Agent ratio         15:0 <sup>1</sup> Native resolution         FHD (1920 x 1000) <sup>14</sup> Resolutions supported         64.0 x 400; 00.0 x 600; 124.0 x 760; 124.0 x 760; 128.0 x 720; 128.0 x 102.4; 144.0 x 900; 1600 x 900; 1600 x 105; 1920 x 108.0           Displey feature         On screen controls: Low blue light mode; Anti-glare           User controls         Bright measure           Displey size (dispont), meth)         60.5 cm (2.3 m)           Ports         100.4 x 1000; 192.0 x 1000           Displey size (dispont), meth)         0.0 s cm (2.3 m)           Ports         100.4 x 1000; 192.0 x 1000; 192.0 x 1000; 192.0 x 1000           Displey size (dispont), meth)         0.0 s cm (2.3 m)           Ports         Displey size (dispont), meth)           Displey size (dispont), meth)         Displex (disture)           Displex size (dispont), meth)         Displex (disture)           Displex size (dispont), meth)         Displex (disture)           Displex size (dispont), meth)         Displex (disture)      <	*Product image may differ from actual product	
Bighness         250 ms1           Contrast ratio         3000:11           Response Ratio         Smc SLG (with over drive) <sup>3</sup> Product colour         Black           Aspect ratio         FL6 J           Native resolution         FL6 J           Read/usion supported         640 490,720 x 400,800 x 600,1024 x 766;1280 x 720;1280 x 800,1024 x 1440 x 900;1600 x 900;1680 x 1050;1920 x 1080           Display features         On-screen controls Low Size light mode; Anti-glare           User controls         Bright mode; Anti-glare           User controls         Bright mode; Anti-glare           Display size dispond, metrid         Go 5 cm (23 n)           Ports and Connectors         1 VGA; 1 H9M1 1.4           Environmental         Operating temperature 5 to 35°C; Operating temperature 5 to 35°C; Operature 5 to 35°	Display type	VA
Contrast ratio         3000.11           Response Ratio         Smc GG (with overdme) <sup>1</sup> Product tolour         Black           Aspect ratio         16.9 <sup>1</sup> Native resolutions         Fillo (1920 × 1080) <sup>1/2</sup> Resolutions supported         640 × 400; 800 × 600; 1024 × 766; 1280 × 720; 1280 × 800; 1024, 1440 × 900; 1600 × 900; 1680 × 1050; 1920 × 1080           Display features         On-screen controls; Low blue light mode, Anti-glare           User controls         Brightness; hup control; Management; Information; Esit; Color control; Image control; Nenu control; Menu control           Display features         On-screen: controls; Low blue light mode, Anti-glare           Derivation Static (1990 × 100 × 2000)         60.5 cm (23.81)           Ports and Connectors         1 VGA; 1 H0M1 1.4           Environmental         Operating temperature: 5 to 35°C; Operating temperature: 5 to 35°C; Mice 35°C; Mic	Panel Active Area	52.59 x 29.58 cm
Response Ratio         Sms GLG (with overdwe) <sup>1</sup> Product colour         Black           Aspect ratio         16.9 <sup>1</sup> Native resolution         PHD (1920 x 1080) <sup>1/2</sup> Resolutions supported         640 x 480; 720 x 400; 800 x 600; 1024 x 766; 1280 x 720; 1280 x 800; 1280 x 1024; 1440 x 900; 1680 x 1050; 1920 x 1080           Display feature         On screen controls; Low blue light mode; Anti-glar           User controls         Brightness; input control, Management; Information; Exit; Color control; Power control; Menu control           Parts and Connecture         1 VGA; 1 HJMH 1.4           Ports and Connecture         100 - 240 VAC SQ/60 Hz           Power         100 - 240 VAC SQ/60 Hz           Power consumption         30 W thrain-main, 2.0 W (hypical), 0.5 W (standby)           Dimensions         53.89 x 5.14 x 32.36 cm (Without stand.)           Physical accurity features         Security Lock-ready <sup>1/a</sup> Ecolabels         EPAP* registered; 100 Certified configurations available <sup>6</sup> ; ENERGY 51AP <sup>6</sup> ; PCC (50.0241-307; PCC); CD 0241-307; PCC); CD 0241-307; PCC; CD 02	Brightness	250 nits <sup>1</sup>
Product colour         Black           Aspect ratio         16-91           Aspect ratio         16-91           Resolutions supported         640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 1024; 1440 x 900; 1500 x 900; 1580 x 1056; 1920 x 1080           Display features         On-screen controls; Low blue light mode: Anti-glare           Display features         On-screen controls; Low blue light mode: Anti-glare           Display size (lalgonal, metric)         60.5 cm (23.87)           Perts and Connectors         1 V6A: 1 H0M 1.4           Environmental         Operating temperature 5 to 35°C;           Dimensions         53.89 x 5.14 x 23.36 cm (Munot stand.)           Power         100 - 240 VAC 50/60 Hz           Dimensions         53.89 x 5.14 x 23.36 cm (Munot stand.)           Physical security features         Security lock ready. <sup>10</sup> Catalabet         EPEAT*registeree. TOO Certified configurations available <sup>4</sup> ; ENERGY 51AR* certified           Catalabet         EPEAT*registeree. TOO Certified configurations available <sup>4</sup> ; ENERGY 51AR* certified           Catalabet         EPEAT*registeree. TOO Certified configurations available <sup>4</sup> ; ENERGY 51AR* certified           Catalabet         EPEAT*registeree. TOO Certified configurations available <sup>4</sup> ; ENERGY 51AR* certified           Catalabet impact specifications         Molited paper pulp cushon inside box is 100%	Contrast ratio	3000:1 <sup>1</sup>
Aspect ratio         16:9 <sup>1</sup> Native resolution         FH0 (1920 × 1080) <sup>1/2</sup> Resolutions supported         640 × 400, 720 × 400, 800 × 600; 1024 × 766; 1280 × 720; 1280 × 800; 1280 × 1024; 1440 × 900; 1600 × 900; 1680 × 1050; 1920 × 1080           Display features         On-5creen controls; Low blue light mode: Anti-glare           User controls         Brightness; Input control, Management; Information; Exit; Color control; Image control, Power control, Menu control           Display Size diagonal, metrix)         Operating immedity: 20 10 906 RH;           Power         100 - 240 VKG 50/60 Hz           Power on 100 - 240 VKG 50/60 Hz         Power on 300 (maximum, 200 (typical), 0.5 V (standby)           Dimensions         53.89 × 5.14 × 32.35 cm (Without stand.)           Weight         3.57 kg (Wth stand.)           Physical security features         Security lock-ready <sup>10</sup> Certification NOM, PSB, RoHS, SEPA, TCO Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC: ISD 9241-307; KC/KCC, Mcrosoft WHOL Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC: ISD 9241-307; KC/KCC, Mcrosoft WHOL Certification, NOM, PSB, RoHS, SEPA, TCO Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC: ISD 9241-307; KC/KCC, Mcrosoft WHOL Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC: ISD 9241-307; KC/KCC, Mcrosoft WHOL Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC: ISD 9241-307; KC/KCC, Mcrosoft WHOL Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC: ISD 9241-307; KC/KCC, Mcrosoft WHOL Certified Configurations available <sup>4</sup> , ENERGY STAR <sup>6</sup> , PCC	Response Ratio	5ms GtG (with overdrive) <sup>1</sup>
Native resolution         FHD (1920 × 1080) <sup>1/2</sup> Resolutions supported         640 × 480; 720 × 400; 800 × 600; 1024 × 768; 1280 × 702; 1280 × 1024; 1440 × 900; 1600 × 900; 1600 × 1005; 1920 × 1080           Display features         On-screen controls; tow blue light mode; Anti-glare           User controls         Bightness; Input control; Management; Information; Exit; Color control; Power control; Power control; Menu control           Display size (diagonal, metrid)         60.5 cm (23.87)           Ports and Connectors         1 V64; 1 HM1 1.4           Environmental         Operating temperature 5 to 35°C;           Domaining temperature 5 to 35°C;         Demaining temperature 5 to 35°C;           Domaining temperature 5 to 100% RH;         Power           Power         100 - 240 VAC 50/60 Hz           Power toorsumption         30 W (maximum), 20 W (typical), 0.5 W (standby)           Dimensions         53.89 x5.1 x3.23.5 cm (Without stand.)           Weight         3.57 kg (With stand.)           Physical Security fock-ready <sup>10</sup> Ecolabels           EPEM* registered; TOO Certified configurations available <sup>1</sup> ; ENERGY STAR* Certified           Colabels         EPEM* registered; TOO Certified configurations available <sup>1</sup> ; ENERGY STAR* Certified           Colabels         EPEM* registered; TOO Certified configurations available <sup>1</sup> ; ENERGY STAR* Certified           Sustainable impact specificati	Product colour	Black
Resolutions supported         640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 800; 1280 x 1024; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080           Display features         On-screen controls: Low blue light mode: Anti-glare           User controls         Brightness: liput control; Management; Information; Esit; Color control; Image control; Power control; Menu control           Display size (diagonal, metric)         60 5 cm (23.83           Ports and Connectors         1 VGA; 1 HDM1.1.4           Operating thumotity: 20 to 80% RH;           Power         100 - 240 VAC 50/60 Hz           Power onsumption         30 W (maximum), 20 W (lypical), 0.5 W (standby)           Dimensions         53.89 x 5.14 x 32.36 cm (Without stand.)           Weight         3.57 kg (With stand.)           Physical security features         Security Lock-ready <sup>10</sup> Ecolabels         EPEAT® registered; TCO Certified configurations available <sup>6</sup> , ENERGY STAR® cartified           Certification and compliance         Australian-New Zaeland MEPS, Bits, BSHR, BSKI, BCC, CE, CECP, CEL, CSA; EAC, ENERGY STAR®, ECC, Stores, TUV FL, WCC; Microsoft WHQL, Certificat, NMM, PSB, KoHS, STAP, TCO Certified; COC, ETITIEd Configurations, Resolution, RES, WEEE, SC, China Fanegy           Data CCL (Cace Z, Californa Energy Commission (ECC), WW application, RES, WEE, SC, China Fanegy           Diversion (WM) PSB, KoHS, STAP, TCO Certified; COC, ETITIEd Configurations, RES, STAP, TCO Certified; Configurations, RES, STAP, TCO Certified; C	Aspect ratio	16:9 <sup>1</sup>
Display features         On-screen controls: Low bloe light mode; Anti-glare           User controls         Brightness; hput control, Management; Information; Exit; Color control; Image control; Power control; Menu control           Display size (diagonal, metric)         60.5 cm (23.8)*           Parts and Connectors         1 VGA; 1 HDM1 1.4           Diperating temperature: 5 to 35°C; Operating temperature: 5 to 60.6 RH;           Power         100 - 240 VAC 50060 Hz           Power consumption         30 W (maximum), 200 W (typical), 0.5 W (standby)           Dimensions         5.3 89, x5.14 x3.2.3 6 cm (Without stand.)           Weight         3.5.7 kg (With stand.)           Physical security features         Security lock-ready. <sup>10</sup> Catalabels         EPEAT** egistered: TCC Certified configurations available <sup>4</sup> ; ENERCY STAR** certified           Catalabel         Australian-New Zealand MEPS; BB; SDS KD; CC; CC; CEP, CEE, CS; EX, EX, CC; SD 9241-307; KZ/KCC; Microsoft WHQL Certification and compliance           Certification and compliance         Australian-New Zealand MEPS; BB; SDS KD; CC; CC; CEP, CEE, CS; EX, EX, CC; CH, ELE, VS; EX, CC; CH, ELE, VS; EX, VS; CC EX, EXE, CS; EXE, VS; CC EXE, EXE, VS; SDS VS; CC CC; CE; CEP, CEE, VS; EXE, VS; CS INS, VS; CC; CE; CEE, VS; EXE, VS; CC EXE, EXE, VS; SDS VS; CC CC; CE; CEP, CEE, CS; EXE, CS; CS; EXE, VS; CC EXE, EXE, VS; SDS VS; CC CC; CE; CEP, CEE, VS; EXE, VS; CS INS, VS; CC INS, VS; CE, VS; SD VS; CC INS, VS; CS INS, VS; CC INS, VS;	Native resolution	FHD (1920 x 1080) <sup>1,2</sup>
User controls         Brightness: Input control; Management; Information; Exit; Color control; Image control; Power control; Menu control           Dipplaysize (diagonal, metric)         60.5 cm (23.8")           Ports and Connectors         1 VGA; 1 HDMI 1.4           Environmental         Operating temperature: 5 to 35"C; Operating humility, 20 to 80% RH;           Power         100 - 24 0 VAC 50/60 Hz           Power         100 - 24 0 VAC 50/60 Hz           Power consumption         30 W (rpaximum), 20 W (typical), 0.5 W (standby)           Dimensions         53.89 x 51.4 x 32.3 c cm (Without stand.)           Weight         3.57 kg (with stand.)           Physical security features         Security lock-ready <sup>10</sup> Ecolabels         EPEAM® registered; TCO Certified configurations available <sup>6</sup> : ENERGY STAR®, ECC, ISO 9241-307; KC/KCC, Microsoft WHQL Certification; NOK, PSB, RoHS; SENA; TCO certified Edge; TVU UB; VCC; Vicc; Waram, MEPS; SW, SEE; SC; Dina Energy Label (CED) Grade 2; California Energy Commission (CEC); Waramity and; Quick Setup Poster; Do cAtt; AC power cord <sup>6</sup> Sustainable Impact specifications         Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; SSW, ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box         Molder paper pulp cushion inside box is 100% sustainably sourced and recyclable; SSW, ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> Wetcal weingr angle         178°           Panel bit d	Resolutions supported	640 × 480; 720 × 400; 800 × 600; 1024 × 768; 1280 × 720; 1280 × 800; 1280 × 1024; 1440 × 900; 1600 × 900; 1680 × 1050; 1920 × 1080
Display size (diagonal, metric)       6.0.5 cm (23.8°)         Ports and Connectors       1 VGA; 1HOM 1.4         Environmental       Operating temperature: 5 to 35°C.         Power       100 - 240 VAC 50160 Hz.         Power onsumption       30 W (maximum), 20 W (spical), 0.5 W (standby)         Dimensions       53.89 x 5.14 x 32.3 6 cm (Without stand.)         Weight       3.57 kg (With stand.)         Physical security features       Security lock-ready <sup>10</sup> Ecolabelis       EPEAPT registered: TOC Certified configurations available <sup>4</sup> ; ENERGY STAR® (certified         Certification and compliance       Australian-New Zealand MEPS; BISS (Str); CEC; CECP, CEL; CSC, ENERGY STAR®, FCC; ISO 9241-307; KC/KCC; Microsoft WHOI, Certification NOM PSB; SchSS; StrA; TOC certified TGO entrified TGO entread entrecy class and enauxies and entrified TGO entrif	Display features	On-screen controls; Low blue light mode; Anti-glare
Ports and Connectors         1 VGA; 1 HDMI 1.4           Environmental         Operating temperature: 5 to 35°C; Operating tumingty: 20 to 80% RH;           Power         100 - 240 VAC 50/60 Hz           Power onsumption         30 W (tryainut), 20 W (typical), 0.5 W (standby)           Dimensions         53.89 x 51.4 x 23.67 cm (Without stand.)           Weight         3.57 kg (With stand.)           Physical security features         Security lock-ready <sup>10</sup> Ecolabels         EPEAH* registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR <sup>4</sup> , ECC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification and compliance         Cartification File Standback (CC) CHE; ECCP; CEL; CSA; EAC; ENERGY STAR <sup>4</sup> , ECC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification and compliance           Sustainable impact specifications         Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; B5% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box         Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>8</sup> Panels bit depth         B bit (6 bit + FRC)           Vestard lewing angle         178°           Horizontal Vewing angle         178°           VESA mounting         100 mm × 100 mm <sup>12</sup> Hardness         3H           Screen treatment         Anti-glare           Ricker-free         Yes (TÜV certified)	User controls	Brightness; Input control; Management; Information; Exit; Color control; Image control; Power control; Menu control
Construction         Operating temperature: S to 35°C; Operating turnidity: 20 to 80% RH;           Power         100 - 240 WK 50% CoHz           Power consumption         30 W (maximum), 20 W (typical), 0.5 W (standby)           Dimensions         53.89 x 5.14 x 32.36 cm (Without stand.)           Weight         3.57 kg (With stand.)           Physical security features         Security lock-ready <sup>10</sup> Ecolabels         EPEAT* registered: TCO Certified configurations available <sup>6</sup> ; ENERGY STAR® certified           Certification and compliance         Australian-New Zealand MEPS; BIS, SBMI; CB, CCC; CE; CEC, CSA; EAC; NERGY STAR®, PCI, SO 9241-307; KC/KCC, Microsoft WHQL (Certification: NOM; PSB; RoHS; SBM; ICO Certified Edge; TUV Bauer; TUV BL; VCC; Victnam MEPS; WEEE; ISC; Chin Benergy Label (EEL) Grade 2; California Energy Cormission (EE); WW application; (E; UAE; UKraine certificates; NRES of South Africa; TUV Flicker free certified           Sustainable impact specifications         Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box         Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>6</sup> Pasels per inch (ppl)         93 ppi           Panel bit depth         8 bit (6 bit + FRC)           Vertical viewing angle         178°           Horizontal viewing angle         178°           Scied micro-edge         11	Display size (diagonal, metric)	60.5 cm (23.8")
Environmental         Operating humidity: 20 to 80% RH;           Power         100 - 240 VAC 50/60 Hz           Power consumption         30 W (maximum, 20 W (typical), 0.5 W (standby)           Dimensions         53.89 x 5.14 x 32.36 cm (Without stand.)           Weight         3.57 kg (With stand.)           Physical security lock-ready. <sup>10</sup> Ecolabels           Ecolabels         EPEAT® registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR®; ECC; ISO 9241-307; K/KCC; Microsoft WHQL           Certification and compliance         Certification: NOMP, SPS, RNDS; SEB, XTO Certified; TCO CERIFIEd;	Ports and Connectors	1 VGA; 1 HDMI 1.4
Power consumption         30 W (traxinum), 20 W (typical), 0.5 W (standby)           Dimensions         53.89 x 5.1 4 x 32.36 cm (Without stand.)           Weight         3.57 kg (With stand.)           Physical security features         Security lock-ready <sup>10</sup> Ecolabels         EPEAT® registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR® certified           Australian-New Zealand MEPS; BPS; BSM; Gis; CCC; CE; CEP; CLS; CA; EA; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL           Certification and compliance         Australian-New Zealand MEPS; BPS; BSM; Gis; CCC; CE; CEP; CLS; CA; EA; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL           Sustainable impact specifications         Molided paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box         Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup> Pixels per inch (ppl)         93 ppi           Panel bit depth         8 bit (6 bit + FRC)           Vertical viewing angle         178°           Horizontal viewing angle         178°           Vertical viewing angle         178°           Vertical viewing angle         100 mm x 100 mm <sup>12</sup> Hardness         3H           Screen treatment         Anti-glare           Flicker-free         Yes (TÜV certified)	Environmental	
Dimensions       53.89 x 5.14 x 32.36 cm (Without stand.)         Weight       3.57 kg (With stand.)         Physical security features       Security lock-ready <sup>10</sup> Ecolabels       EPEAT <sup>®</sup> registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR <sup>®</sup> certified         Certification and compliance       Australian-New Zealand MEPS; BS; BSMIL CB; CCC; CE: ICE LC: CSA; EAC; ENERGY STAR <sup>®</sup> , FCC; ISO 9241-307; KC/KCC; Microsoft WHQL         Certification and compliance       Australian-New Zealand MEPS; BS; BSMIL CB; CCC; CE: ICE LC: CSA; EAC; ENERGY STAR <sup>®</sup> , FCC; ISO 9241-307; KC/KCC; Microsoft WHQL         Sustainable impact specifications       Moldied paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box       Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>®</sup> Pixels per inch (ppi)       93 ppi         Panel bid depth       8 bit (6 bit + FRC)         Vertical viewing angle       178°         Horizontal viewing angle       178°         Vertical viewing angle       178°         VESA mounting       100 mm x 100 mm <sup>12</sup> Hardness       3H         Screen treatment       Anti-glare         Flicker-free       Yes (TUV certified)         Low bull light modes       Yes (TUV certified)         Display scan freq	Power	100 - 240 VAC 50/60 Hz
Weight       3.57 kg (With stand.)         Physical security features       Security lock-ready <sup>10</sup> Ecolabels       EPEAT <sup>ere</sup> registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR® certified         Certification and compliance       Australian-New Yealand MEPS; BIS; BSMI; CG; CC; CE; CECP, CEL; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL         Certification and compliance       Certification in MPS; BIS; BSMI; CG; CC; CE; CECP, CEL; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL         Sustainable impact specifications       Molded paper pub cushion inside box is 100% sustainably sourced and recyclable; BS% ITE-derived closed loop plastic; Low Halogen <sup>6,7,3</sup> What's in the box       Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power card <sup>8</sup> Pkels per inch (pol)       93 ppi         Panel bit depth       8 bit (6 bit + FRC)         Vertical viewing angle       178°         Horizontal viewing angle       178°         Bezel       3-sided micro-edge         Tit       -5 to +23°         VESA mounting       100 mm x 100 mm <sup>12</sup> Harchess       3H         Screen treatment       Anti-glare         Flicker-free       Yes (TÜV certified)         Display scan frequency (vertical)       48-75 Hz         Display scan frequency (vorticantal)       55.6.90.8 k	Power consumption	30 W (maximum), 20 W (typical), 0.5 W (standby)
Physical security features         Security lock-ready <sup>10</sup> Ecolabels         EPEAT® registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR® certified           Certification and compliance         Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CCD; CE; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification; NQM, PSB; ReHS; SEPA; TCO Certified (pc); TUV Ball; YCC; Vict) Vietnam MEPS; WEEF; ISC; China Energy Label (ECL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; UX-raine certificates; NRCS of South Africa; TUV Flicker free certified           Sustainable impact specifications         Molded paper putp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box         Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup> Pixels per inch (ppi)         93 ppi           Panel bit depth         8 bit (6 bit + FRC)           Vertical viewing angle         178°           Bezel         3-sided micro-edge           Tilt         -5 to +23°           VESA mounting         100 mm 1 <sup>2</sup> Hardness         3H           Screen treatment         Anti-glare           Ricker-free         Yes (TÜV certified)           Low blue light modes         Yes (TÜV certified)           Display scan frequency (vertical)         48-75 Hz           Display scan f	Dimensions	53.89 x 5.14 x 32.36 cm (Without stand.)
Ecolabels         EPEAT* registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR* certified           Australian-New Zealand MEPS; BS; BSMI; CB; CCC; CE; CEP; CEL; CAS; EAC; ENERGY STAR*; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL, Certification and compliance           Sustainable impact specifications         Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Cow Halogen <sup>6,7,8</sup> What's in the box         Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup> Pixels per inch (ppi)         93 ppi           Panel bit depth         8 bit (6 bit + FRC)           Vertical viewing angle         178*           Bezel         3-sided micro-edge           Titt         -5 to +23*           VESA mounting         100 mm x 100 mm <sup>12</sup> Hardness         3H           Screen treatment         Anti-glare           Elcker-free         Yes (TÚV certified)           Display scan frequency (vertical)         48-75 Hz           Display scan frequency (vertical)         55.6-9.0 kHz           Display scan frequency (vertical)         55.6-9.0 kHz           Display colors         Up to 16.7 million colors supported <sup>3</sup>	Weight	3.57 kg (With stand.)
Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification; NOM; PSB; RoHS; SEPA; TCO Certified; Edge; TUV Bauart; TUV LBI; VCC; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); Ww application; ICE; UAE; Ukraine certificates; NRCS of South Africa; TÜV Flicker free certified           Sustainable impact specifications         Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the box         Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup> Pixels per inch (ppi)         93 ppi           Panel bit depth         Bbit (6 bit + FRC)           Vertical viewing angle         178°           Bezel         3-sided micro-edge           Tilt         -5 to + 23°           VESA mounting         100 mm x 100 mm <sup>12</sup> Hardness         3H           Screen treatment         Anti-glare           Flicker-free         Yes (TÜV certified)           Low blue light modes         Yes (TÜV certified)           Display scan frequency (horizontal)         55.6-90.8 kHz           Pixel pixth         0.27 x 0.27 mm           Display colors         Up to 16.7 million colors supported <sup>3</sup>	Physical security features	Security lock-ready <sup>10</sup>
Certification: NOM. PSB; RoHS; SEPA; TOC certified; TOC vertified; VUR Bauer; TUV Bauer; TUV LBL; VCCI; Vietnam MEPS; WEEE; ISC; China Energy certifiedSustainable impact specificationsMolded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup> What's in the boxMonitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup> Pixels per inch (ppi)93 ppiPanel bit depth8 bit (6 bit + FRC)Vertical viewing angle178°Horizontal viewing angle178°Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TUV certified)Low blue light modesYes (TUV certified)Display scan frequency (vertical)5.5-9.08. kHzPixel pich0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display color Gamut72% NTSC	Ecolabels	EPEAT® registered; TCO Certified configurations available <sup>4</sup> ; ENERGY STAR® certified
What's in the boxMonitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup> Pixels per inch (ppi)93 ppiPanel bit depth8 bit (6 bit + FRC)Vertical viewing angle178°Horizontal viewing angle178°Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Certification and compliance	Certification; NOM; PSB; RoHS; SEPA; TCO Certified; TCO Certified Edge; TUV Bauart; TUV LBL; VCCI; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; NRCS of South Africa; TÜV Flicker free
Pixels per inch (ppl)93 ppiPanel bit depth8 bit (6 bit + FRC)Vertical viewing angle178°Horizontal viewing angle178°Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Sustainable impact specifications	Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% ITE-derived closed loop plastic; Low Halogen <sup>6,7,8</sup>
Panel bit depth8 bit (6 bit + FRC)Vertical viewing angle178°Horizontal viewing angle178°Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	What's in the box	Monitor; HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord <sup>9</sup>
Vertical viewing angle178°Horizontal viewing angle178°Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Pixels per inch (ppi)	93 ppi
Horizontal viewing angle178°Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Panel bit depth	8 bit (6 bit + FRC)
Bezel3-sided micro-edgeTilt-5 to +23°VESA mounting100 mm x 100 mm <sup>12</sup> Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Vertical viewing angle	178°
Tilt       -5 to +23°         VESA mounting       100 mm x 100 mm <sup>12</sup> Hardness       3H         Screen treatment       Anti-glare         Flicker-free       Yes (TÜV certified)         Low blue light modes       Yes (TÜV certified)         Display scan frequency (vertical)       48-75 Hz         Display scan frequency (horizontal)       55.6-90.8 kHz         Pixel pitch       0.27 x 0.27 mm         Display colors       Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut       72% NTSC	Horizontal viewing angle	178°
VESA mounting       100 mm x 100 mm <sup>12</sup> Hardness       3H         Screen treatment       Anti-glare         Flicker-free       Yes (TÜV certified)         Low blue light modes       Yes (TÜV certified)         Display scan frequency (vertical)       48-75 Hz         Display scan frequency (horizontal)       55.6-90.8 kHz         Pixel pitch       0.27 x 0.27 mm         Display colors       Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut       72% NTSC	Bezel	3-sided micro-edge
Hardness3HScreen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Tilt	-5 to +23°
Screen treatmentAnti-glareFlicker-freeYes (TÜV certified)Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	VESA mounting	100 mm x 100 mm <sup>12</sup>
Flicker-free       Yes (TÜV certified)         Low blue light modes       Yes (TÜV certified)         Display scan frequency (vertical)       48-75 Hz         Display scan frequency (horizontal)       55.6-90.8 kHz         Pixel pitch       0.27 x 0.27 mm         Display colors       Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut       72% NTSC	Hardness	3Н
Low blue light modesYes (TÜV certified)Display scan frequency (vertical)48-75 HzDisplay scan frequency (horizontal)55.6-90.8 kHzPixel pitch0.27 x 0.27 mmDisplay colorsUp to 16.7 million colors supported <sup>3</sup> Display Color Gamut72% NTSC	Screen treatment	Anti-glare
Display scan frequency (vertical)       48-75 Hz         Display scan frequency (horizontal)       55.6-90.8 kHz         Pixel pitch       0.27 x 0.27 mm         Display colors       Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut       72% NTSC	Flicker-free	Yes (TÜV certified)
Display scan frequency (horizontal)     55.6-90.8 kHz       Pixel pitch     0.27 x 0.27 mm       Display colors     Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut     72% NTSC	Low blue light modes	Yes (TÜV certified)
Pixel pitch     0.27 × 0.27 mm       Display colors     Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut     72% NTSC	Display scan frequency (vertical)	48-75 Hz
Display colors     Up to 16.7 million colors supported <sup>3</sup> Display Color Gamut     72% NTSC	Display scan frequency (horizontal)	55.6-90.8 kHz
Display Color Gamut 72% NTSC	Pixel pitch	0.27 x 0.27 mm
	Display colors	Up to 16.7 million colors supported <sup>3</sup>
Management software HP Display Center; HP Display Manager <sup>11</sup>	Display Color Gamut	72% NTSC
	Management software	HP Display Center; HP Display Manager <sup>11</sup>

# HP P24v G5 FHD Monitor

# Accessories and services (not included)



# HP P24v G5 FHD Monitor

#### Messaging Footnotes

All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lov 2 Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store.
 HPD Display Manager software agent must be running on a web server and host PC. Some limitations may apply to legacy monitors.
 Based on US EPEA1® registration according to EEE 1680.1-2018 EPEA1®. EPEA1® status varies by country. Visit www.epeat.net for more information.

<sup>5</sup> TE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680-1210 standard. <sup>6</sup> 100% outer box/corrugate cushion packaging made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic material. Any plastic cushions are made from >90% recycled plastic. Excludes plastic bags and plastic toam sheeting. <sup>7</sup> Recycling facilities not available in all locations. <sup>9</sup> PLD Sight Wanager software agent must be running on a web server and host PC. Some limitations may apply to legacy monitors. <sup>9</sup> Compatible with all P GS Series displays and these select mini PCs: EliteDesk 800 G6, EliteDesk 805 G6, EliteDesk 805 G8, EliteDesk 805 G9, EliteDesk 80

#### Technical Specifications Footnotes

<sup>1</sup> All specifications represent the typical specifications provided by HPs component manufacturers; actual performance may vary either higher or lower.
 <sup>2</sup> HDMI 1.4 or VGA required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or VGA. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 a to BB and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 a to BB and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 a to BB and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 a to BB and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one HDMI or vGA. The video card of the connected PC must be capable of supporting 1920 x 1080 at 60 Hz with 8-bit color using an external device at the connected PC must be capable of supporting the target of the connected PC must be capable of supporting target of the connected PC must be capable of supporting target of the connected PC must be capable of support target of the connected PC must be capable of support target of the connected PC must be capable of support target of target of

information

Information. 6 Molded pulp cushions are made from 100% recycled wood fiber and organic materials. 7 External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen. 8 ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard. 9 Included cables may vary by country. 10 Lock sold separately. 11 HP Display Center requires Windows 10 (or higher) on host PC and is available from the Windows store.

<sup>12</sup> Mounting hardware sold separately.

Sign up for updates hp.com/go/getupdated

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

