
### **Technical Specifications**



1. Power Button

### **Technical Specifications**

### HP Z27u G3 QHD USB-C Display



- 1. OSD control
- 2. Security cable slot
- **3.** Master power switch
- **4.** Power connector
- 5. HDMI port
- **6.** DisplayPort connector
- 7. DisplayPort connector OUT

#### Back

- **8.** USB Type-C<sup>™</sup> port with DP Alt Mode 1.4, USB upstream data, and maximum power delivery up to 100 W
- 9. RJ-45 (network) jack
- 10. USB port
- **11.** USB port (Battery charging 1.2, 7.5W)
- 12 USB port
- **13.** USB port (Battery charging 1.2, 7.5W)

#### **Technical Specifications**

Panel Specifications Display Size (Diagonal)
Panel Technology

**IPS Refresh Rate** 60 Hz Panel Bit Depth 8 bit **Aspect Ratio** 16:9 **Brightness (Typical)** 350 nits Contrast Ratio (Static) 1000:1 **Contrast Ratio Minimum (Static)** 700:1 **Dvnamic Contrast Ratio** 10M:1 Flicker Free Yes

**Pixel Pitch** 0.2331(mm) x 0.2331(mm)

Pixels Per Inch (Ppi) 109 PPI Backlight Lamp Life Minimum (To Half 40 k

**Brightness - In Hours)** 

Backlight TypeEdge-litScreen TreatmentAnti-glareHardness3HHaze25%

**Response Time (Typical)** 5ms GtG (with overdrive)

Horizontal Viewing Angle (Typical 178°

Cr>10)

Vertical Viewing Angle (Typical Cr>10) 178°

**Panel Active Area (W X H)** 596.736(H) x 335.66(V)

NOTE: Performance Specifications Represent The Typical Specifications Provided By HP's Component

27"

Manufacturers; Actual Performance May Vary Either Higher Or Lower.

Color sRGB 99 %

**P3 D65** 85%

Color Management Factory Color Calibrated Yes (Delta E <= 2)

**Calibrated Color Presets** sRGB, BT.709, P3 D65 (Production after Jan '21)

**RGB Channel Adjust** Yes, Gain **Default Color Temperature** SRGB

**Monitor Specifications Bezel** 4-sided Micro Edge

Color (Head) Turbo Silver; (Stand) Turbo Silver

 Tilt
 -5 to +20°

 Swivel
 ±45°

 Pivot
 ±90

 Height Adjust Range
 150mm

VESA Mounting 100 mm x 100 mm (bracket included)

Security Lock Ready Standard Security Lock Slot

**Detachable Stand** Yes

Warranty (Number Of Years) 3/3/0 for LA, NA, EMEA, APJ; (3/3/3 in select APJ Countries)
Low Blue Light Mode Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution

certified)

**Display Management Software** HP Display Center

On Screen Display Brightness +, Color, Image, Input, Power, Menu,

Wanagement, Information, Exit **User-Assignable Function Buttons**Yes, 4 buttons

 Native Resolution
 QHD (2560 x 1440)

 Maximum Resolution
 2560 x 1440 @ 60HZ

 Preset Graphic Modes/Suppored
 640 x 480@60Hz

 Resolutions
 800 x 600@60Hz



#### **Technical Specifications**

Technical Specifications				
	High Definition Video Formats  Minimum Vertical Scan Rate	1280 x 720@60Hz 1024 x 768 @ 60Hz 1280 x 1024 @ 60Hz 1440 x 900 @ 60Hz 1600 x 900 @ 60Hz 1600 x 1200 @ 60Hz 1680 x 1050 @ 60Hz 1920 x 1080 @ 60Hz 1920 x 1200 @ 60Hz 2560 x 1440 @ 60Hz 2560 x 1440 @ 60Hz 720 x 480i @ 60Hz 720 x 480p @ 60Hz 1280 x 720p @ 60Hz 1920 x 1080i @ 60Hz 1280 x 720p @ 50Hz 1920 x 576i @ 50Hz 1280 x 720p @ 50Hz 1280 x 720p @ 50Hz 1920 x 1080i @ 50Hz 1920 x 1080p @ 60Hz 1920 x 1080p @ 60Hz		
	Maximum Vertical Scan Rate	60 Hz		
	Minimum Horizontal Scan Rate	30.0 kHz		
	Maximum Horizontal Scan Rate	90.0 kHz		
	Maximum Pixel Clock User Programmable Modes	250 MHz 10		
	_	10 (English, Spanish, German, French, Italian, Netherlands,		
	Languages	Portuguese, Japanese, T-Chinese and S-Chinese)		
Connector Types	DisplayPort™ DisplayPort™ Out HDMI USB Type-C™ Video Input	1 DisplayPort™ 1.4 1 DisplayPort™ 1.4-out 1 HDMI 2.0 1 USB Type-C™ (DP Alt Mode 1.4, power delivery up to 100W)		
	USB- A	4 USB-A 3.2 Gen1 (2 for battery charging 1.2, 7.5W)		
	Ethernet	Yes		
Special Features	Picture-in-Picture, Picture-by-Picture	Yes		
	DaisyChain/DisplayPort Multi stream	Yes		
	Transport (MST) User Updateable Firmware	Yes		
Power & Operating	Power Supply	Internal		
Specs	Power Source	100 – 240 VAC 50 / 60 Hz		
•	Power Consumption- MAX	160 W		
	Energy Saving/Stand By Mode	0.5 W		
	Power Consumption- Typical	39 W		
	Power Cable Length	1.9 m		
ENERGY STAR Data	Operational Mode at 100 VAC	21.33W		
	Operational Mode at 115 VAC	21.36W		
	Operational Mode at 230 VAC	21.44W		
Eu Energy Efficiency Class (ERP lot-5)	On-mode Power Consumption	23.7W		



#### **Technical Specifications**

	Annual Power Consumption Energy Efficiency Class	35 kWh F
Operating Conditions	Operating Temperature - Celsius	5° – 35°C
	Operating Temperature - Fahrenheit	41° – 95°F
	Non-Operatin Temperature - Celsius	−34° − 60°C

Non-Operating Temperature -Fahrenheit

**Operating Humidity** 20 – 80% Relative Humidity (non-condensing)

29° - 140°F

**Non-Operating Humidity** 5-95%

Operating Altitude 0 - 5.000 m (16.400 ft.) 0-12.192 m (40,000 ft.) **Non-operating Altitude** 

**Environmental Features and Certifications** 

Mercury-free LED display backlighting

**Agency Approvals and Certifications** 

**Arsenic-Free Display Glass** Yes

Low Halogen Yes

WW application

CE,CB,KC/KCC/NOM/PSB/EAC/GS/TUV-S/ISO 9241-307/

Low Blue Light/ BIS/cTUVus/CCC/CEL/CECP/SEPA/Energy Star/TCO/TCO Certified

Yes, Mercury-free LED backlighting

Edge/VCCI/FCC/BSMI/WEEE/UAE/Ukraine/ERP/ISC

**Microsoft WHQL Certification** Yes **ENERGY STAR® Certified** Yes **EPEAT®** Registered Yes Regions need to verify by country

CEL Grade 1 **China Energy Label** 

TCO Certified Edge Yes **TCO Certified** Yes

SmartWay Transport Partnership - NA

only

Yes (NA sku)

**Contains Recycled Plastics** 

**Contains Recycled Plastics** 81.06%

Recyclable Packaging (Box, packing

materials)

100% recyclable packaging.

Metric

Unit Product/Package **Specifications** 

	PIECHIC	illiperiat
<b>Product Dimensions</b> (Unpacked with stand) (W x D x H)	61.23 x 20.5 x 53.04 cm	24.11 x 8.07 x 20.88 in
Product Dimensions (Packed) (W x D x H)	69.8 x 42.3 x 16.3 cm	27.48 x 16.65 x 6.42 in
<b>Display Head Dimensions</b> (Unpacked without stand) (W x D x H)	61.23 x 3.89x 35.61 cm	24.11 x 1.53 x 14.02 in
Base Area Footprint (w x d mm)	246 x 205 mm	9.69 x 8.07 in
Bezel Measurement	601.8 mm	23.69 in
Product Weight (Unpacked with stand)	6.2 kg	13.7 lb
Product Weight (Packed)	9.4 kg	20.7 lb
Product Weight (Head Only)	4.7 kg	10.36 lb

What's in the box?

Documentation kit DP1.4 Cable (1.8m)

HDMI 2.0 cable (1.8m, Production after May'21)



Imperial

### **Technical Specifications**

USB 3.2 Gen2 Type C to C (1m)

Power cable VESA Adapter Cable Holder

User Guide and Warranty Languages **User Guide Languages** 

**Warranty Languages** 

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Turkish.

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.



### **Technical Specifications**

Copyright © 2021 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



### Summary

Change Log			
enange 20g			
January 12, 2021	V1 to V2	Update	Technical Specifications
February 28,2021	V2 to V3	Update	Energy Efficiency Class
April 16, 2021	V3 to V4	Update	VESA Mounting Specs
June 1, 2021	V4 to V5	Update	Color Management
June 24, 2021	V5 to V6	Update	What's in the box? section
March 22, 2023	V6 to V7	Update	VESA Mounting specs
	V7 to V8		

